EC1000 BLANKET & ROLLER WASH

Issued: 18/07/03 Revision No: 1

Page: 1

E C S (Nottingham) Ltd Cross Road Annesley Cutting Annesley Nottinghamshire NG15 0AL Tel: 01623 720444 Fax: 01623 720445

1. Наименование на веществото / препарата и на фирмата / предприятието

1. Паименование на веществото / препарата и на фирмата / предприятието		
Product name:	EC1000 BLANKET & ROLLER WASH	
CAS number:	64742-48-9	
Product code:	EC1000	
Use / description of product:	Complex Mixture Aliphatic Cycloparaffinic hydrocarbons.	
2. Състав на препарата / информация за компонентите		
Ingredient 1:	LOW BOILING POINT HYDROGEN TREATED NAPHTHA – NAPHTHA (PETROLEUM), HYDROTREATED HEAVY 99%	
	CAS: 64742-48-9	
	EINECS: 265-150-3	
Ingredient 2:	[-] R10; [Xn] R65; [Xi] R66;	
	ISOPROPYLAMINE ALKYL BENZENE SULPHONATE 1%	
	CAS: 68584-24-7	
	EINECS: 271-531-5	
	[Xi] R36;	
3. Описание на опасностите		
Main hazards:	Harmful: may cause lung damage if swallowed.	
4 Мерки за оказване на първа помощ (Симптоми)		

4. Мерки за оказване на първа помощ (Симптоми)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. Мерки за оказване на първа помощ (Действия)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. See doctor if necessary.

EC1000 BLANKET & ROLLER WASH

Issued: 18/07/03 Revision No: 1

Page: 2

Ingestion:	Immediately rinse mouth and provide fresh air. Do not induce vomiting. Seek medical attention.
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Seek medical attention
5. Мерки при гасене на пожар	
Extinguishing media:	Water spray. Dry chemical powder. Alcohol or polymer foam. Do not use water jet, as this may will spread fire.
Exposure hazards:	Cool closed containers exposed to fire with a water spray.
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.
6. Мерки при аварийно изпускане	

Personal precautions:	Refer to section 8 of SDS for personal protection details.
Environmental precautions:	Do not discharge into drains or rivers.
Clean-up procedures:	Absorb into dry earth or sand.
. Работа с веществото / препарата и съхранение	

Handling requirements: Ensure there is sufficient ventilation of the area.

Storage conditions:	Store in cool, well ventilated area. Keep away from sources of ignition. Keep container
	tightly closed. Keep away from direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure all engineering
	mentioned in section 7 of SDS are in place.
Respiratory protection:	Adequate ventilation When the vapour concentration is to high, filter mask.
Hand protection:	Protective gloves made of nitrile.
Eye protection:	Safety goggles.
Skin protection:	Chemical resistant standard issue work clothes.
TWA (8 hr exposure limit):	150ppm

9. Физични и химични свойства

State:	Liquid
Colour:	Pale yellow
Odour:	Sweet-smelling
Evaporation rate:	0.04
Solubility in water:	Slightly soluble
Boiling point/range°C:	180-217
Flammability limits %:	0,60
upper:	7,00
Flash point ^o C:	62

EC1000 BLANKET & ROLLER WASH

Issued: 18/07/03 Revision No: 1

Page: 3

Autoflammability°C:	>200	
Vapour pressure:	0.04KpA@20c	
Relative density:	790kg/m	
10. Стабилност и реактивоспособнос		
Stability:	Stable under normal conditions.	
Conditions to avoid:	Flames. Heat. Sources of ignition.	
Materials to avoid:	Strong oxidising agents.	
11. Токсикологическа информация		
Effects of exposure:	Aspiration Hazard- Do not breathe Vapour or spray May Cause lung damage if material gets into the lungs after accidental swallowing or vomiting of ingested material	
Ingredient 1:	LOW BOILING POINT HYDROGEN TREATED NAPHTHA – NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	
Ingredient 2:	ISOPROPYLAMINE ALKYL BENZENE SULPHONATE ORL RAT LD50 >2000mg/Kg	
12. Информация за околната среда		
Mobility:	Absorbed only slowly into soil.	
Persistence and degradability: Expected to be inherently biodegradable		
Bioaccumulative potential:	Bioaccumulation potential.	
13. Третиране на отпадъците		

Waste disposal:Recover and reclaim or recycle. Otherwise incinerate. Disposal should be dealt with only
by qualified personnel familiar with the specific substance.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. Информация за транспортиране

ADR / RID

Shipping name: Not Classified as Dangerous Substance.

IMDG / IMO

IATA / ICAO

15. Информация, съгласно действащата нормативна уредба

Hazard symbols: Harmful.

EC1000 BLANKET & ROLLER WASH

Issued: 18/07/03 Revision No: 1

Page: 4



Risk phrases: R65: Harmful: may cause lung damage if swallowed. Safety phrases: S23: Do not breathe vapour. S24: Avoid contact with skin. S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. S43: In case of fire, use Carbon Dioxide, Foam. NEVER USE WATER Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions. 16. Друга информация R10: Flammable. Risk phrases used in s.2: R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking. R36: Irritating to eyes. Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage

resulting from handling or from contact with the above product.

САМО ЗА ПРОМИШЛЕНА УПОТРЕБА