



Информация за продукт: CtP-developer V432.18L

Описание на продукта:	Plate developer - ready-for-use
Област на използване:	Suitable for digital plate types with a spectral sensitivity of 830 nm Electra Excel, HRO, HRL - KPG Arte IP-21 - Ipagsa Brillia LH-PCE, LH-PSE, LH-LPI - Fuji
Особености:	excellent developing results low consumption no sludge building process in the developing machines no affect on machine parts density: 1,08 g/cm ³ pH-value: 13 colour: yellowish flash point: > 100°C
Начин на употреба:	<u>Replenisher quantity:</u> approx. 140 ml/m ² of CtP-developer V432.18L approx. 60 - 80 ml/m ² of CtP-replenisher V437.18 (only at low plate consumption under approx. 30 printing plates/day) <u>Developing temperature:</u> 24 - 26°C, depending on the type of plate and the developing machine (max. temp. 26°C) <u>Processing time:</u> approx. 30 - 40 sec., depending on the type of plate <u>Speed:</u> high rotation speed, approx. 80-90 % (Attention! Pay attention to the instructions of the plate manufacturer!) <u>Durability:</u> 3 - 4 weeks (in compliance with the given handicaps)
Бележки:	protect against frost
Бройка/количество:	20 l, 200 l
Обяснителна бележка:	To measure the developer by the conductivity is not exactly enough on the V432.18L. Although the developer remains stable by the addition of the mentioned replenisher the conductivity reduces a little bit.