

Page 1/7

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 20.08.2010

1 Identification of the substance/preparation and of the company/undertaking

· Product details

Trade name: ANTISTAT SPRAY 10X400ML

• Article number: 02002D06

· Application of the substance / the preparation: Anti-static agent

 Manufacturer/Supplier: FUJIFILM EUROPE NV EUROPARK-NOORD 21-22 9100 SINT-NIKLAAS BELGIUM TEL: +32 3 760 02 00 FAX: +32 3 776 91 22

• Further information obtainable from: productsafety@fujifilm.eu • Information in case of emergency: +32 3 760 02 00

2 Hazards identification

· Hazard description:



Xi Irritant F+ Extremely flammable N Dangerous for the environment

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

R 12 Extremely flammable.

R 38 Irritating to skin.

- R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

100.0 % by mass of the contents are flammable

Keep out of the reach of children

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

· Chemical characterization

Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 106-97-8 butane EINECS: 203-448-7 **b** F+; R 12 30-50%

(Cont. on page 2)



Page 2/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 20.08.2010

Trade name: ANTISTAT SPRAY 10X400ML

	(Cont	. from page 1)
CAS: 75-28-5	isobutane	20-40%
EINECS: 200-857-2	🔥 F+; R 12	
CAS: 74-98-6	propane	10-20%
EINECS: 200-827-9	🔥 F+; R 12	
CAS: 31394-54-4	heptane	5-10%
EINECS: 250-610-8	🗙 Xn, 🗙 Xi, 🔥 F, 🏪 N; R 11-38-50/53-65-67	
CAS: 73513-42-5	hexane, isomers	3-7%
	🔀 Xn, 🔀 Xi, 🐞 F, 🏪 N; R 11-38-51/53-65-67	
CAS: 108-87-2	methylcyclohexane	0.5-1.5%
EINECS: 203-624-3	🗙 Xn, 🗙 Xi, 🔥 F, 🏪 N; R 11-38-51/53-65-67	
CAS: 109-66-0	pentane	0.1-1%
EINECS: 203-692-4	🔀 Xn, 🔥 F+, 🏪 N; R 12-51/53-65-66-67	
CAS: 110-54-3	n-hexane	0.1-1%
EINECS: 203-777-6	Repr. Cat. 3; 🗙 Xn, 🗙 Xi, 🔥 F, 🏪 N; R 11-38-48/20-62-	
	51/53-65-67	
 Additional information 	tion: For the wording of the listed risk phrases refer to section 16.	

4 First aid measures

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Protective equipment: No special measures required.

6 Accidental release measures

- Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
 Measures for environmental protection:
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting: Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- · Information for safe handling:
- Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

(Cont. on page 3)

GB



*

Page 3/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Revision: 20.08.2010

Trade name: ANTISTAT SPRAY

Printing date 07.09.2010

Trade name: ANTISTAT SPRAY 10X400ML
(Cont. from page 2) • Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50℃, i.e. electric lights. Do not pierce or burn, even after use. Do not spray onto a naked flame or any incandescent material.
 Storage: Requirements to be met by storerooms and receptacles: Store in a cool location. Observe official regulations on storing packagings with pressurized containers. Information about storage in one common storage facility: Not required. Further information about storage conditions: Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. Storage class: 2B
8 Exposure controls/personal protection • Additional information about design of technical facilities: No further data; see item 7.
Ingredients with limit values that require monitoring at the workplace:
106-97-8 butane WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
• Additional information: The lists valid during the making were used as basis.
 Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the skin. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Protection of hands:
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Cont. on page 4) - GB



Page 4/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Revision: 20.08.2010

(Cont. from page 3)

Printing date 07.09.2010

Trade name: ANTISTAT SPRAY 10X400ML

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical	properties
· General Information	Data of section 9 only applicable on liquid part
· Form:	Liquid
· Colour: · Odour:	Colourless Characteristic
 Change in condition Melting point/Melting range Boiling point/Boiling range 	
· Flash point:	-25°C
 Ignition temperature: 	250℃
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
· Explosion limits:	
Lower:	1 Vol %
Upper:	7.5 Vol %
 Vapour pressure at 20℃: 	150 hPa
· Density at 20℃:	0.714 g/cm³
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
 Solvent content: VOC (EC) 	100.00 %

10 Stability and reactivity

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Cont. on page 5)

⁻ GB



Page 5/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Trade name: ANTISTAT SPRAY 10X400ML

· Materials to be avoided:

- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological information

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

· Product:

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

 European 	waste	catalogue
------------------------------	-------	-----------

	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
	gases in pressure containers and discarded chemicals
16 05 04*	gases in pressure containers (including halons) containing dangerous substances

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

(Cont. on page 6)

GB

(Cont. from page 4)

Revision: 20.08.2010



Page 6/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Trade name: ANTISTAT SPRAY 10X400ML

(Cont. from page 5)

Revision: 20.08.2010

· Land transport ADR/RII	D (cross-border)
· ADR/RID class:	2 5F Gases.
· Danger code (Kemler):	
· UN-Number:	1950
Packaging group:	-
· Hazard label:	2.1
 Description of goods: Tunnel restriction code 	
· IMDG Class:	2.1
· UN Number:	1950
· Label	
 Label Packaging group: 	1950 2.1 -
 Label Packaging group: EMS Number: 	1950 2.1 - F-D,S-U
 Label Packaging group: 	1950 2.1 - F-D,S-U No
 Label Packaging group: EMS Number: Marine pollutant: 	1950 2.1 - F-D,S-U No AEROSOLS
 Label Packaging group: EMS Number: Marine pollutant: Proper shipping name: 	1950 2.1 - F-D,S-U No AEROSOLS
 Label Packaging group: EMS Number: Marine pollutant: Proper shipping name: Air transport ICAO-TI at ICAO/IATA Class: 	1950 2.1 - F-D,S-U No AEROSOLS nd IATA-DGR: 2.1
 Label Packaging group: EMS Number: Marine pollutant: Proper shipping name: Air transport ICAO-TI at ICAO/IATA Class: UN/ID Number: 	1950 2.1 - F-D,S-U No AEROSOLS nd IATA-DGR: 2.1 1950
 Label Packaging group: EMS Number: Marine pollutant: Proper shipping name: Air transport ICAO-TI at ICAO/IATA Class: 	1950 2.1 - F-D,S-U No AEROSOLS nd IATA-DGR: 2.1

15 Regulatory information

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Cont. on page 7)



Page 7/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Trade name: ANTISTAT SPRAY 10X400ML

· Code letter and hazard designation of product:



Xi Irritant F+ Extremely flammable

N Dangerous for the environment

· Risk phrases:

- 12 Extremely flammable.
- 38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

23 Do not breathe aerosol.

- 24 Avoid contact with skin.
- 51 Use only in well-ventilated areas.
- 61 Avoid release to the environment. Refer to special instructions/safety data sheets.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

100.0 % by mass of the contents are flammable

Keep out of the reach of children

Classification in accordance with Directive 75/324/EEC: Extremely flammable

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases

- 11 Highly flammable.
- 12 Extremely flammable.
- 38 Irritating to skin.
- 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 62 Possible risk of impaired fertility.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- Creation Date 30.11.2009
- * Data modified compared to previous version.

GB -

(Cont. from page 6)

Revision: 20.08.2010