

Page 1/7

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 06.09.2010

# 1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: EASYCOAT ID UV 2364 GLOSS 5KG

- Article number: 12718D04
- · Application of the substance / the preparation: UV curable varnishes for offset printing
- Manufacturer/Supplier: FUJIFILM Europe NV EUROPARK-NOORD 21-22 9100 SINT-NIKLAAS BELGIUM TEL: +32 3 760 02 00 FAX: +32 3 776 91 22

• Further information obtainable from: productsafety@fujifilm.eu • Information in case of emergency: +32 3 760 02 00

# **2 Hazards identification**

· Hazard description:



Xi Irritant N Dangerous for the environment

#### · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

 $\bar{R}$  36/37/38 Irritating to eyes, respiratory system and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### · Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

# **3 Composition/information on ingredients**

### · Chemical characterization

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compo	nents:	
CAS: 42978-66-5 EINECS: 256-032-2	tripropyleneglycol diacrylate X i, 🏪 N; R 36/37/38-43-51/53	20-40%
CAS: 52408-84-1 NLP: 500-114-5	glycerine propoxylate triacrylate Xi; R 36	5-10%
CAS: 119-61-9 EINECS: 204-337-6	benzophenone Xi; R 36/38-52/53	1-5%
CAS: 24650-42-8 EINECS: 246-386-6	2,2-dimethoxy-1,2-diphenylethan-1-one	1-5%
	arylammoniumchloride C, 🔀 Xn, 🌄 N; R 22-34-50	0.1-1%
		ont. on page 2)



Printing date 07.09.2010

Revision: 06.09.2010

### Trade name: EASYCOAT ID UV 2364 GLOSS 5KG

(Cont. from page 1) • Additional information: For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact:

- Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
- I Skin initiation continues, consult a doc

# · After eye contact:

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

# **5** Fire-fighting measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Protective equipment: No special measures required.

## 6 Accidental release measures

- · Person-related safety precautions: Not required.
- Measures for environmental protection:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

## 7 Handling and storage

- · Handling:
- Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location. Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 12

(Cont. on page 3)

GB

Page 2/7



Printing date 07.09.2010

Revision: 06.09.2010

### Trade name: EASYCOAT ID UV 2364 GLOSS 5KG

(Cont. from page 2)

Page 3/7

### 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### • Eye protection:



Tightly sealed goggles

# **9** Physical and chemical properties

### · General Information

Form: Colour: Viscous Colourless

(Cont. on page 4)



Printing date 07.09.2010

Revision: 06.09.2010

### Trade name: EASYCOAT ID UV 2364 GLOSS 5KG

	(Cont. from page
Odour:	Characteristic
<ul> <li>Change in condition Melting point/Melting range: Boiling point/Boiling range:</li> </ul>	
· Flash point:	Not applicable.
· Danger of explosion:	Product does not present an explosion hazard.
· Density at 20°C:	1.05 g/cm <sup>3</sup>
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Insoluble.
· Viscosity: Kinematic at 20℃:	300 s (DIN 53211/4)
<ul> <li>Solvent content: VOC (EC)</li> </ul>	0.40 %

# 10 Stability and reactivity

 $\cdot$  Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Materials to be avoided:
- Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

# **11 Toxicological information**

- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

• Sensitisation May cause sensitisation by skin contact.

# **12 Ecological information**

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

(Cont. on page 5)

Page 4/7

GB



Printing date 07.09.2010

Revision: 06.09.2010

(Cont. from page 4)

### Trade name: EASYCOAT ID UV 2364 GLOSS 5KG

Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

### 13 Disposal considerations

#### · Product:

#### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

### · European waste catalogue

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 03 00 wastes from MFSU of printing inks

08 03 99 wastes not otherwise specified 16.2.2001 L 47/13 Official Journal of the European

· Uncleaned packaging:

Communities EN

• **Recommendation:** Disposal must be made according to official regulations.

· Land transport AD	R/RID (cross-border)
· ADR/RID class:	9 Miscellaneous dangerous substances and articles.
· Danger code (Keml	ler): 90
· UN-Number:	3082
<ul> <li>Packaging group:</li> </ul>	
<ul> <li>Hazard label:</li> </ul>	9
<ul> <li>Special marking:</li> </ul>	Symbol (fish and tree)
Description of good	ds: 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUIE N.O.S. (TRIPROPYLENEGLYCOL DIACRYLATE, 2,2-DIMETHOXY-1,2 DIPHENYLETHAN-1-ONE)
· Tunnel restriction of	
· Maritime transport	IMDG:
· IMDG Class:	9
LINI Muunahaan	3082
· UN Number:	



Page 6/7

# Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 06.09.2010

### Trade name: EASYCOAT ID UV 2364 GLOSS 5KG

	(Cont. from page :
· Packaging group:	
· EMS Number:	F-A,S-F
<ul> <li>Marine pollutant:</li> </ul>	Yes
-	Symbol (fish and tree)
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (TRIPROPYLENEGLYCOL DIACRYLATE, 2,2-DIMETHOXY-1,2 DIPHENYLETHAN-1-ONE)
· Air transport ICAO-TI a	nd IATA-DGR:
· ICAO/IATA Class:	9
· UN/ID Number:	3082
· Label	9
<b>–</b>	
<ul> <li>Packaging group:</li> </ul>	

# 15 Regulatory information

### • Labelling according to EU guidelines: The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xi Irritant N Dangerous for the environment

- $\cdot$  Hazard-determining components of labelling:
- tripropyleneglycol diacrylate
- · Risk phrases:
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 43 May cause sensitisation by skin contact.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- · Safety phrases:
- 24 Avoid contact with skin.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 37 Wear suitable gloves.
- 61 Avoid release to the environment. Refer to special instructions/safety data sheets.

(Cont. on page 7)

GB



Γ

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 06.09.2010

#### Trade name: EASYCOAT ID UV 2364 GLOSS 5KG

(Cont. from page 6)

	ormation is based on our present knowledge. However, this shall not constitute a guarante specific product features and shall not establish a legally valid contractual relationship.
· Releva	nt R-phrases
22	Harmful if swallowed.
34	Causes burns.
36	Irritating to eyes.
36/37/3	8 Irritating to eyes, respiratory system and skin.
36/38	Irritating to eyes and skin.
43	May cause sensitisation by skin contact.
50	Very toxic to aquatic organisms.
50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aqua environment.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquate environment.
52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquar environment.
· Creatio	n Date 25.09.2009
· * Data	modified compared to previous version.

Page 7/7