

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 03.09.2010

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** **FLEXOPUR L** **12X1L**
- **Article number:** 11008D04
- **Application of the substance / the preparation:** Washing fluid for offset printing machines
- **Manufacturer/Supplier:**
FUJIFILM Europe NV
EUROPARK-NOORD 21-22
9100 SINT-NIKLAAS
BELGIUM
TEL: +32 3 760 02 00
FAX: +32 3 776 91 22
- **Further information obtainable from:** productsafety@fujifilm.eu
- **Information in case of emergency:** +32 3 760 02 00

2 Hazards identification

- **Hazard description:**










Xi Irritant

- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
R 10 Flammable.
R 36 Irritating to eyes.
R 67 Vapours may cause drowsiness and dizziness.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol	 Xi,  F; R 11-36-67	15-30%
CAS: 107-98-2 EINECS: 203-539-1	1-methoxy-2-propanol	R 10	10-20%
CAS: 107-21-1 EINECS: 203-473-3	ethanediol	 Xn; R 22	3-7%
CAS: 97043-91-9	Alcohols, C9-16 ethoxylated	 Xn,  Xi; R 22-41	1-5%
CAS: 1336-21-6 EINECS: 215-647-6	ammonia	 C,  N; R 34-50	0.1-1%

(Cont. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 03.09.2010

Trade name: FLEXOPUR L 12X1L

(Cont. from page 1)

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

5 Fire-fighting measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

7 Handling and storage

- **Handling:**
- **Information for safe handling:** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Store only in the original receptacle.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Cont. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 03.09.2010

Trade name: FLEXOPUR L	12X1L
-------------------------------	--------------

(Cont. from page 2)

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
-----	--

107-98-2 1-methoxy-2-propanol

WEL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
-----	---

107-21-1 ethanediol

WEL	Short-term value: 104** mg/m ³ , 40** ppm Long-term value: 10* 52** mg/m ³ , 20** ppm Sk *particulate **vapour
-----	--

· Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Cont. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 03.09.2010

Trade name: FLEXOPUR L	12X1L
-------------------------------	--------------

(Cont. from page 3)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Liquid
Colour:	Colourless
Odour:	Alcohol-like

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Undetermined.

· **Flash point:** 26°C

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Density at 20°C:** 0.968 g/cm³

· **Solubility in / Miscibility with water:** Fully miscible.

· **pH-value at 20°C:** 11.2

· **Solvent content:**
VOC (EC) 41.85 %

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **Materials to be avoided:**

· **Dangerous reactions** No dangerous reactions known.

· **Dangerous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

· **Acute toxicity:**

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

(Cont. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 03.09.2010

Trade name: FLEXOPUR L 12X1L

(Cont. from page 4)

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

07 00 00	WASTES FROM ORGANIC CHEMICAL PROCESSES
07 06 00	wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics
07 06 04*	other organic solvents, washing liquids and mother liquors

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information

· **Land transport ADR/RID (cross-border)**



· **ADR/RID class:** 3 Flammable liquids.

· **Danger code (Kemler):** 30

· **UN-Number:** 1993

· **Packaging group:** III

· **Hazard label:** 3

· **Description of goods:** 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), 1-METHOXY-2-PROPANOL)

(Cont. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 03.09.2010

Trade name: FLEXOPUR L 12X1L

(Cont. from page 5)

· Tunnel restriction code D/E

· Maritime transport IMDG:



- **IMDG Class:** 3
- **UN Number:** 1993
- **Label** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), 1-METHOXY-2-PROPANOL)

· Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1993
- **Label** 3
- **Packaging group:** III
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), 1-METHOXY-2-PROPANOL)

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xi Irritant

· **Hazard-determining components of labelling:**

propan-2-ol

· **Risk phrases:**

- 10 Flammable.
- 36 Irritating to eyes.
- 67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

- 7 Keep container tightly closed.
- 16 Keep away from sources of ignition - No smoking.

(Cont. on page 7)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 03.09.2010

Trade name: FLEXOPUR L 12X1L

(Cont. from page 6)

24/25 Avoid contact with skin and eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**

10 Flammable.

11 Highly flammable.

22 Harmful if swallowed.

34 Causes burns.

36 Irritating to eyes.

41 Risk of serious damage to eyes.

50 Very toxic to aquatic organisms.

67 Vapours may cause drowsiness and dizziness.

- **Creation Date** 12.06.2009

- *** Data modified compared to previous version.**