



# Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 03.09.2010

### 1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: FR IS 4X5L

· Article number: 143514

· Application of the substance / the preparation: Washing fluid for offset printing machines

· Manufacturer/Supplier:

FUJIFILM Europe NV

**EUROPARK-NOORD 21-22** 

9100 SINT-NIKLAAS

**BELGIUM** 

TEL: +32 3 760 02 00 FAX: +32 3 776 91 22

· Further information obtainable from: productsafety@fujifilm.eu

Information in case of emergency: +32 3 760 02 00

#### 2 Hazards identification

· Hazard description:







Xn Harmful

F Highly flammable

N Dangerous for the environment

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 11 Highly flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 67 Vapours may cause drowsiness and dizziness.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

## 3 Composition/information on ingredients

- · Chemical characterization
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compor	nents:	
	heptane Xn, Xi, F, N; R 11-38-50/53-65-67	60-80%
CAS: 108-87-2 EINECS: 203-624-3	methylcyclohexane Xn, Xi, N F, N; R 11-38-51/53-65-67	15-30%
	propan-2-ol  X Xi,	10-20%
	cyclohexane Xn, Xi, N F, N; R 11-38-50/53-65-67	0.5-1.5%
	(Co	ont. on page 2)

711 page 2)



IIIDS

according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 03.09.2010

Trade name: FR IS 4X5L

(Cont. from page 1)

Page 2/7

· Additional information: For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.

### 5 Fire-fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

## 7 Handling and storage

- · Handling:
- · Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

#### 8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Cont. on page 3)





## Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 03.09.2010

Trade name: FR IS 4X5L

(Cont. from page 2)

	(Cont. from page 2)	
· Ingredients with limit values that require monitoring at the workplace:		
142-8	2-5 heptane	
WEL	Long-term value: 500 ppm	
67-63-0 propan-2-ol		
WEL	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm	
110-8	2-7 cyclohexane	
WEL	Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm	

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

GB



Page 4/7

# Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 03.09.2010

Trade name: FR IS 4X5L

(Cont. from page 3)

9 Physical and chemical properties		
General Information		
Form: Colour: Odour:	Liquid Colourless Characteristic	
<ul> <li>Change in condition</li> <li>Melting point/Melting range:</li> <li>Boiling point/Boiling range:</li> </ul>		
· Flash point:	-4℃	
· Danger of explosion:	Product is not explosive. However, formation of explosive ai vapour mixtures are possible.	
· Density at 20℃:	0.718 g/cm³	
· Solubility in / Miscibility with water:	Partly soluble.	
· Solvent content: VOC (EC)	99.95 %	

## 10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Materials to be avoided:
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: Carbon monoxide and carbon dioxide

## 11 Toxicological information

- · Acute toxicity:
- · LD/LC50 values relevant for classification:

#### 108-87-2 methylcyclohexane

Oral LD50 2250 mg/kg (mouse)

### 110-82-7 cyclohexane

Oral LD50 12705 mg/kg (rat)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

(Cont. on page 5)





# Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 03.09.2010

Trade name: FR IS 4X5L

(Cont. from page 4)

## 12 Ecological information

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

## 13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

•	European waste catalogue	
07 00 00	WASTES FROM ORGANIC CHEMICAL PROCESSES	
07 06 00	wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics	
07 06 04*	other organic solvents, washing liquids and mother liquors	

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 Flammable liquids.

Danger code (Kemler): 33
UN-Number: 1206
Packaging group: II
Hazard label: 3

· Description of goods: 1206 HEPTANES, solution

(Cont. on page 6)



Page 6/7

# Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 03.09.2010

Trade name: FR IS 4X5L

(Cont. from page 5)

- · Tunnel restriction code D/E
- · Maritime transport IMDG:



IMDG Class: 3
UN Number: 1206
Label 3
Packaging group: II
EMS Number: F-E,S-D

Marine pollutant: No\_\_\_\_

· Proper shipping name: HEPTANES, solution

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3 · UN/ID Number: 1206 · Label 3 · Packaging group: II

· Proper shipping name: HEPTANES, solution

### 15 Regulatory information

#### · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:







Xn Harmful

F Highly flammable

N Dangerous for the environment

Hazard-determining components of labelling:

heptane

#### · Risk phrases:

- 11 Highly flammable.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.

#### · Safety phrases:

- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition No smoking.

(Cont. on page 7)



Page 7/7

# Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 03.09.2010

Trade name: FR IS 4X5L

(Cont. from page 6)

- 23 Do not breathe vapour
- 24 Avoid contact with skin.
- 33 Take precautionary measures against static discharges.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 57 Use appropriate container to avoid environmental contamination.
- 60 This material and its container must be disposed of as hazardous waste.
- 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant R-phrases

- 11 Highly flammable.
- 36 Irritating to eyes.
- 38 Irritating to skin.
- 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.
- · Creation Date 13.07.2009
- · \* Data modified compared to previous version.

GB