

Page 1/6

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 24.08.2010

1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: ISOPROPYLALCOHOL 200LT

· Article number: 984583

· Application of the substance / the preparation: Fountain additive for offset printing

Manufacturer/Supplier:
 FUJIFILM EUROPE NV
 EUROPARK-NOORD 21-22
 9100 SINT-NIKLAAS

BELGIUM

TEL: +32 3 760 02 00 FAX: +32 3 776 91 22

- · Further information obtainable from: productsafety@fujifilm.eu
- · Information in case of emergency: +32 3 760 02 00

2 Hazards identification

· Hazard description:





Xi Irritant

F Highly flammable

· Information concerning particular hazards for human and environment:

R 11 Highly flammable.

R 36 Irritating to eyes.

R 67 Vapours may cause drowsiness and dizziness.

3 Composition/information on ingredients

- · Chemical characterization:
- · CAS No. Description 67-63-0 propan-2-ol
- · Identification number(s)
- EINECS Number: 200-661-7 Index number: 603-117-00-0

4 First aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

- GB



Page 2/6

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 24.08.2010

Trade name: ISOPROPYLALCOHOL 200LT

(Cont. from page 1)

5 Fire-fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Protective equipment: No special measures required.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- · Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from frost.
- · Storage class: 3

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Cont. on page 3)



Page 3/6

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 24.08.2010

Trade name: ISOPROPYLALCOHOL 200LT

(Cont. from page 2)

- · Respiratory protection: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties		
· General Information		
Form:	Liquid	
Colour:	Colourless	
Odour:	Alcohol-like	
· Change in condition		
Melting point/Melting rang		
Boiling point/Boiling rang	le : 82℃	
· Flash point:	12℃	
· Ignition temperature:	350℃	
· Danger of explosion:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.	
· Explosion limits:		
Lower:	2 Vol %	
Upper:	12 Vol %	
· Vapour pressure at 20℃:	43 hPa	
· Density at 20℃:	0.787 g/cm ³	
	(Cont. on page	

GB



Page 4/6

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 24.08.2010

Trade name: ISOPROPYLALCOHOL 200LT

(Cont. from page 3)

· Solubility in / Miscibility with

water: Fully miscible.

· Viscosity:

Dynamic at 20℃: 2.08 mPas

· Solvent content:

VOC (EC) 100.00 %

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Materials to be avoided:
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

· LD/LC50 values relevant for classification:

67-63-0 propan-2-ol

	-	
Oral	LD50	5045 mg/kg (rat)
	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.

12 Ecological information

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Cont. on page 5)



Page 5/6

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 24.08.2010

Trade name: ISOPROPYLALCOHOL 200LT

(Cont. from page 4)

· European waste catalogue		
07 00 00	WASTES FROM ORGANIC CHEMICAL PROCESSES	
07 07 00	wastes from the MFSU of fine chemicals and chemical products not otherwise specified	
07 07 99	wastes not otherwise specified	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 Flammable liquids.

Danger code (Kemler): 33
UN-Number: 1219
Packaging group: II
Hazard label: 3

· Description of goods: 1219 ISOPROPANOL (ISOPROPYL ALCOHOL)

· Tunnel restriction code D/E

· Maritime transport IMDG:



· IMDG Class: 3
· UN Number: 1219
· Label 3
· Packaging group: II

• EMS Number: F-E,S-D • Marine pollutant: No

· Proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3 · UN/ID Number: 1219 · Label 3 · Packaging group: II

(Cont. on page 6)



Page 6/6

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 24.08.2010

Trade name: ISOPROPYLALCOHOL 200LT

(Cont. from page 5)

· Proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





Xi Irritant

F Highly flammable

- · Risk phrases:
- 11 Highly flammable.
- 36 Irritating to eyes.
- 67 Vapours may cause drowsiness and dizziness.
- · Safety phrases:
- 7 Keep container tightly closed.
- 16 Keep away from sources of ignition No smoking.
- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Creation Date 15.05.2009
- · * Data modified compared to previous version.

- GE