

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 24.08.2010

### 1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** **STABILAT D**                      **1100KG**
- **Article number:** FS0206
- **Application of the substance / the preparation:** Fountain additive for offset printing
- **Manufacturer/Supplier:**  
 FUJIFILM Europe NV  
 EUROPARK-NOORD 21-22  
 9100 SINT-NIKLAAS  
 BELGIUM  
 TEL: +32 3 760 02 00  
 FAX: +32 3 776 91 22
- **Further information obtainable from:** productsafety@fujifilm.eu
- **Information in case of emergency:** +32 3 760 02 00

### 2 Hazards identification

- **Hazard description:**








Xi Irritant

- **Information concerning particular hazards for human and environment:**  
 The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.  
 R 43 May cause sensitisation by skin contact.
- **Classification system:**  
 The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

### 3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 56-81-5 EINECS: 200-289-5	glycerol	10-20%
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol  Xi,  F; R 11-36-67	5-10%
CAS: 55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one  T,  C,  N; R 23/24/25-34-43-50/53	<0.1%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 24.08.2010

**Trade name: STABILAT D 1100KG**

(Cont. from page 1)

### 4 First aid measures

- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

### 5 Fire-fighting measures

- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Person-related safety precautions:** Not required.
- **Measures for environmental protection:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

### 7 Handling and storage

- **Handling:**
- **Information for safe handling:** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:** No special measures required.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Store only in the original receptacle.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from frost.
- **Storage class:** 10

### 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

**56-81-5 glycerol**WEL | Long-term value: 10 mg/m<sup>3</sup>

(Cont. on page 3)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 24.08.2010

<b>Trade name: STABILAT D</b>	<b>1100KG</b>
-------------------------------	---------------

(Cont. from page 2)

**67-63-0 propan-2-ol**

<b>WEL</b>	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 999 mg/m <sup>3</sup> , 400 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling

### 9 Physical and chemical properties

- **General Information**

<b>Form:</b>	Liquid
<b>Colour:</b>	Blue
<b>Odour:</b>	Mild

- **Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** 82°C

- **Flash point:** 36°C

- **Danger of explosion:** Product does not present an explosion hazard.

- **Vapour pressure at 20°C:** 23 hPa

- **Density at 20°C:** 1.082 g/cm<sup>3</sup>

(Cont. on page 4)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 24.08.2010

**Trade name: STABILAT D 1100KG**

(Cont. from page 3)

- |  |                 |
|--|-----------------|
| · <b>Solubility in / Miscibility with water:</b> | Fully miscible. |
| · <b>pH-value at 20°C:</b>                       | 4.9             |
| · <b>Solvent content: VOC (EC)</b>               | 7.00 %          |

### 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Materials to be avoided:**
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
  - **on the skin:** No irritant effect.
  - **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant
- **Sensitisation** May cause sensitisation by skin contact.

### 12 Ecological information

- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### 13 Disposal considerations

- **Product:**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

06 00 00	WASTES FROM INORGANIC CHEMICAL PROCESSES
06 03 00	wastes from the MFSU of salts and their solutions and metallic oxides

(Cont. on page 5)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 24.08.2010

**Trade name: STABILAT D 1100KG**

(Cont. from page 4)

06 03 14 | solid salts and solutions other than those mentioned in 06 03 11 and 06 03 13

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

### 14 Transport information

- **Land transport ADR/RID (cross-border)**
- **ADR/RID class:** -

- **Maritime transport IMDG:**
- **IMDG Class:** -
- **Marine pollutant:** No

- **Air transport ICAO-TI and IATA-DGR:**
- **ICAO/IATA Class:** -

### 15 Regulatory information

- **Labelling according to EU guidelines:**  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- **Code letter and hazard designation of product:**



Xi Irritant

- **Hazard-determining components of labelling:**  
mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one
- **Risk phrases:**  
43 May cause sensitisation by skin contact.
- **Safety phrases:**  
24 Avoid contact with skin.  
37 Wear suitable gloves.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**  
11 Highly flammable.  
23/24/25 Toxic by inhalation, in contact with skin and if swallowed.  
34 Causes burns.  
36 Irritating to eyes.

(Cont. on page 6)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 24.08.2010

<b>Trade name: STABILAT D</b>	<b>1100KG</b>
-------------------------------	---------------

(Cont. from page 5)

- 43 May cause sensitisation by skin contact.
- 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 67 Vapours may cause drowsiness and dizziness.
- **Creation Date** 07.05.2009
- \* **Data modified compared to previous version.**

GB