

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 25.08.2010

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** **STABILAT DH 2010** **10KG**
- **Article number:** 01716D06
- **Application of the substance / the preparation:** Fountain additive for offset printing
- **Manufacturer/Supplier:**
FUJIFILM Europe NV
EUROPARK-NOORD 21-22
9100 SINT-NIKLAAS
BELGIUM
TEL: +32 3 760 02 00
FAX: +32 3 776 91 22
- **Further information obtainable from:** productsafety@fujifilm.eu
- **Information in case of emergency:** +32 3 760 02 00

2 Hazards identification

- **Hazard description:**









Xi Irritant

- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
R 43 May cause sensitisation by skin contact.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 56-81-5 EINECS: 200-289-5	glycerol	10-20%
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol  Xn,  Xi; R 20/21/22-36/38	3-7%
CAS: 112-34-5 EINECS: 203-961-6	2-(2-butoxyethoxy)ethanol  Xi; R 36	0.5-1.5%
CAS: 55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one  T,  C,  N; R 23/24/25-34-43-50/53	<0.1%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

GB

(Cont. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 25.08.2010

Trade name: STABILAT DH 2010 10KG

(Cont. from page 1)

4 First aid measures

- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Not required.
- **Measures for environmental protection:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

- **Handling:**
- **Information for safe handling:** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:** No special measures required.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Store only in the original receptacle.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from frost.
- **Storage class:** 12

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

56-81-5 glycerolWEL | Long-term value: 10 mg/m³

(Cont. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 25.08.2010

Trade name: STABILAT DH 2010 10KG

(Cont. from page 2)

111-76-2 2-butoxyethanol

WEL	Short-term value: 50 ppm Long-term value: 25 ppm Sk
-----	---

112-34-5 2-(2-butoxyethoxy)ethanol

WEL	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm
-----	--

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling

9 Physical and chemical properties

- **General Information**

Form:	Liquid
Colour:	Blue
Odour:	Mild

- **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 100°C

- **Flash point:** Not applicable.

- **Danger of explosion:** Product does not present an explosion hazard.

(Cont. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 25.08.2010

Trade name: STABILAT DH 2010 10KG

(Cont. from page 3)

· Vapour pressure at 20°C:	23 hPa
· Density at 20°C:	1.112 g/cm ³
· Solubility in / Miscibility with water:	Fully miscible.
· pH-value at 20°C:	4.4
· Solvent content: VOC (EC)	5.10 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Materials to be avoided:**
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
- **Sensitisation** May cause sensitisation by skin contact.

12 Ecological information

- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Product:**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Cont. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 25.08.2010

Trade name: STABILAT DH 2010 10KG

(Cont. from page 4)

· **European waste catalogue**

06 00 00	WASTES FROM INORGANIC CHEMICAL PROCESSES
06 03 00	wastes from the MFSU of salts and their solutions and metallic oxides
06 03 14	solid salts and solutions other than those mentioned in 06 03 11 and 06 03 13

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information

· **Land transport ADR/RID (cross-border)**

· **ADR/RID class:** -

· **Maritime transport IMDG:**

· **IMDG Class:** -

· **Marine pollutant:** No

· **Air transport ICAO-TI and IATA-DGR:**

· **ICAO/IATA Class:** -

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xi Irritant

· **Hazard-determining components of labelling:**

mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

· **Risk phrases:**

43 May cause sensitisation by skin contact.

· **Safety phrases:**

24 Avoid contact with skin.

37 Wear suitable gloves.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

(Cont. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 25.08.2010

Trade name: STABILAT DH 2010 10KG

- (Cont. from page 5)
- 23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
 - 34 Causes burns.
 - 36 Irritating to eyes.
 - 36/38 Irritating to eyes and skin.
 - 43 May cause sensitisation by skin contact.
 - 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Creation Date** 08.05.2009
 - *** Data modified compared to previous version.**

GB