according to Regulation (EC) No. 1907/2006



Product name : SCHWEGO® CLEANER Z

Revision: 01.09.2009 **Version:** 1.0.0

Print date : 29.03.2010

01. Identification of the substance/mixture and of the company/undertaking

Product name

SCHWEGO® CLEANER Z (8809)

Use of the substance / mixture

Printing chemical for industrial and/or professional use

Manufacturer/Supplier

Bernd Schwegmann GmbH & Co. KG

Street/P.O.Box

Wernher-von-Braun-Str. 14

Country code/Postal code/Town/City

D-53501 Grafschaft-Gelsdorf

Telephone / Telefax

+49 22 25 / 92 26-0 / +49 22 25 / 92 26-48

Contact person Material Safety Data Sheet

E-Mail: MSDS@SchwegmannNet.de

Emergency information

+49 61 31 / 19 24 0 (Universitätsklinikum Mainz)

02. Hazards identification

Classification

Highly flammable. • Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. • Harmful: may cause lung damage if swallowed. • Irritating to eyes and skin.

Classification: F; R 11 · N; R 51/53 · Xn; R 65 · Xi; R 36/38 · R 67

Additional information

The product has skin-degreasing properties

03. Composition/information on ingredients

Chemical characterization

Mixture of organic solvents

Hazardous components

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (BENZENE < 0,1); EC-No.: 265-151-9; CAS-No.: 64742-49-0

Percentage: 35 - 50 %

Classification : F ; R 11 N ; R 51/53 Xn ; R 65 Xi ; R 38 R 67

PROPAN-2-OL; EC-No.: 200-661-7; CAS-No.: 67-63-0

Percentage: 35 - 50 %

Classification : F ; R 11 $\,$ Xi ; R 36 $\,$ R 67

For the wording of the listed risk phrases refer to section 16.

04. First-aid measures

General

Immediately remove all contaminated clothing.

In all cases of doubt, or when symptoms persist, seek medical attention.

After inhalation

Let in fresh air. Call a doctor, should the air passages be affected.

After skin contact

Wash away with soap and water and rinse.

After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.).

After ingestion

Do not induce vomiting.

Page: 1 / 7

according to Regulation (EC) No. 1907/2006



Product name : SCHWEGO® CLEANER Z

Revision: 01.09.2009 **Version:** 1.0.0

Print date : 29.03.2010

Danger of aspiration

Rinse mouth with cold water.

Never give an unconscious person anything by mouth. After first aid treatment immediately seek medical advice.

Notes to a physician

No data available.

05. Fire-fighting measures

Suitable extinguishing media

Water spray jet. Alcohol resistant foam, CO2, powders, water spray.

Unsuitable extinguishing media

Never use a full-power water jet to prevent fire from dispersing and spreading.

Special risk posed by the substance or by the actual mixture, its combustion products or gases discharged

In case of fire, harmful vapors may be generated: Carbon monoxide. Carbon dioxide.

Special protective equipment

When extinguishing fires, use breathing apparatus with an independent source of air.

Additional information

Cool endangered containers with water in case of fire.

Do not allow the quenching water into the sewage system.

06. Accidental release measures

Personal precautions

Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Do not allow discharge into bodies of water, the soil or the sewage system.

Methods for cleaning up/collecting

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Remove according to regulations.

Additional information

Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours. Provide for sufficient ventilation.

07. Handling and storage

Information for safe handling

Avoid contact with skin and eyes.

Normal precautions taken when handling chemicals should be observed.

Information about protection against explosions and fires

Protect liquid against evaporation. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Take precautionary measures against static discharges. Keep away from ignition sources and provide for good ventilation. Electrical facilities must comply with the Explosion Protection Standard.

Ignition group : T3 **Flammable class :** B

Requirements to be met by storerooms and containers

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Store in an area with solvent resistant flooring or on a drip pan, so that the groundwater will remain unaffected if a leak occurs. Other special storage requirements, such as support walls for example, are to be determined by the user, subject to the amount being stored.

Information about separation of incompatible products

Keep away from strong oxidising agents.

Further information about storage conditions

Store containers tightly closed in a cool well ventilated place.

Page: 2 / 7

according to Regulation (EC) No. 1907/2006



SCHWEGO® CLEANER Z Product name:

Revision: 01.09.2009 Version: 1.0.0

Print date: 29.03.2010

> Storage class: 3

Specific uses

Cleaner for offset printing

For further information refer to our technical data sheet.

08. Exposure controls/personal protection

Additional information about engineering measures

Make sure that ventilation is adequate. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Components with critical values that require monitoring at the workplace (exposure limits)

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (BENZENE < 0,1); CAS-No.: 64742-49-0

Specification: TRGS 900 - maximum limit in the atmosphere at the workplace (D)

Parameter: (RCP-Method) 1000 mg/m³ Value: Category: 2(II) Remarks: **AGS** 27.12.2007 Version date: PROPAN-2-OL; CAS-No.: 67-63-0

TRGS 900 - maximum limit in the atmosphere at the workplace (D) Specification:

Value: 200 ppm / 500 mg/m³

Category: 2(II) Remarks: Version date: 01.04.2007

Specification:

TRGS 903 - biological maximum limits (D) Parameter: Acetone / whole blood / end of exposure or shift

50 mg/l Value: 31.03.2004 Version date :

TRGS 903 - biological maximum limits (D) Specification: Parameter: Acetone / urine / end of exposure or shift

Value: 50 mg/l Version date : 31.03.2004 ETHANOL; CAS-No.: 64-17-5

Specification: TRGS 900 - maximum limit in the atmosphere at the workplace (D)

500 ppm / 960 mg/m³ Value:

2(II) Category: Remarks: 01.04.2007 Version date:

References to the thresholds

Recommended analysis methods for workplace readings: See the series of publications by the German Federal Institute for Occupational Safety and Medicine (Bundesanstalt für Arbeitsschutz und Arbeitsmedizin - BAuA)¹

Personal protective equipment

Respiratory protection

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Filter: Filter model A1. Can be used up to a maximum concentration of 1000 ppm.

Refer to breathing protection instruction sheet.

Hand protection

Solvent-resistent protective gloves according EN 420 and EN 374 part 1 - 3 must be worn.

Gloves, for example butyl rubber,

Thick (mm): 0,7

Penetration time (s): > 14400 (LEVEL 5) (Literature value)

Eye protection

Page: 3 / 7

according to Regulation (EC) No. 1907/2006



Product name : SCHWEGO® CLEANER Z

Revision: 01.09.2009 **Version:** 1.0.0

Print date : 29.03.2010

Use safety goggles with side protection, which comply with EN 166:2001.

Environmental precautions

Refer to protective measures listed in section 6.

09. Physical and chemical properties

Image

Form: Liquid. Colour: Blue.

Odour: Like white spirit.

Relevant safety data

Flow time :	(23 °C)		20 - 25	S	ISO cup 4 mm
Melting point / range :		<	-20	°C	literature
Boiling point / range :	(1013 hPa)	>	80	°C	literature
Flash point :		<	5	°C	ISO 1523
Ignition temperature :		>	250	°C	DIN 51794
Lower explosion limit :			0,6	% b.v.	literature
Upper explosion limit :			12	% b.v.	literature
Vapour pressure :	(50°C)	>	0,1	bar	(calculated)
Density:	(20 °C)		0,75	g/cm³	DIN EN ISO 2811-1
Solubility in water :	(20 °C)	<	600	g/l	(calculated)
Flow time :	(20 °C)	<	20	S	DIN-cup 4 mm
Content VOC (EU):			100	%	(calculated)

Additional information

The designation of explosive limits refers to the flammable mixture constituents and not to the overall product. Additional physico-chemical data is unavailable.

10. Stability and reactivity

Conditions to avoid

None, if handled according to order.

Materials to avoid

Reaction with oxidizing agents possible.

Hazardous decomposition products

Lack of ventilation can cause the generation of explosive vapors

11. Toxicological information

Toxicological tests

Acute toxicity, skin irritation, mucous membrane irritation, genetic altering potential and skin sensitivity will be assessed by the manufacturer based on the available component data.

LD50/LC50 values that are relevant for classification

Specification: LD-50 (PROPAN-2-OL; CAS-No.: 67-63-0)

Routes of entry: oral
Test species: rat
Value / dosage: 5840 mg/kg

Additional toxicological information

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EC).

12. Ecological information

Details on elimination (persistance / degradibility)

Possibility to eliminate the product out of sewage:

Oil and fat separators.

Flocculation.

Page: 4 / 7

according to Regulation (EC) No. 1907/2006



Product name : SCHWEGO® CLEANER Z

Revision: 01.09.2009 **Version:** 1.0.0

Print date : 29.03.2010

Biological degradiation / elimination

The product is biodegradable. (Literature value)

Results of PBT assessment

There are no data available on the preparation / mixture itself.

13. Disposal considerations

Substance / mixture

In accordance with local official regulations. Remove in accordance with regulations.

Recommendation

Precise waste material code to be agreed upon with waste disposer

Waste key

EC-Waste Code: 16 03 05

Contaminated packaging

Recommendation

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant.

14. Transport information

Land transport ADR/RID

Classification

Class: 3 Kemlercode: 33 UN number: 1993 Classification-Code: F1

Special provisions: 640D · LQ 4 · Tunnel restriction code: (D/E)

Proper shipping name

FLAMMABLE LIQUID, N.O.S.

Hazardous components

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (BENZENE < 0,1) · ISOPROPANOL

Packaging

Packaging group: II Label: 3

Maritime transport IMDG/GGVSea

Classification

Class: 3 **EmS** number : F-E / <u>S-E</u>

UN number: 1993 Marine Poll.: -

LQ 1 l

Proper shipping name

FLAMMABLE LIQUID, N.O.S.

Hazardous components

BOILING POINT GASOLINE · ISOPROPANOL

Packaging

Packaging group: II Label: 3

Air transport ICAO-TI and IATA-DGR

Classification

Class: 3 **UN number:** 1993

Proper shipping name FLAMMABLE LIQUID, N.O.S.

Hazardous components

BOILING POINT GASOLINE · ISOPROPANOL

Packaging

Packaging group: II Label: 3

Page: 5 / 7

according to Regulation (EC) No. 1907/2006



Product name : SCHWEGO® CLEANER Z

Revision: 01.09.2009 **Version:** 1.0.0

Print date : 29.03.2010

15. Regulatory information

The exposure scenarios for this substances can be retrieved by the company / undertaking under:

Classification according to EC directives

Danger symbol and danger designation



F; Highly flammable



Xn ; Harmful



N; Dangerous for the environment

R-phrases

11 Highly flammable.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

36/38 Irritating to eyes and skin.

Vapours may cause drowsiness and dizziness.

S-phrases

61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or

label.

51 Use only in well-ventilated areas.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

16 Keep away from sources of ignition - No smoking. 23 Do not breathe qas/fumes/vapour/spray

National regulatory information

Water pollution classification Class: 1 according VwVwS

16. Other information

Literature:

1 http://www.baua.de

² http://www.arbeitssicherheit.de

The details in this material safety data sheet satisfy national and EC legislation.

Restrictions on use recommended by the manufacturer

Private consumer are advised not to use this product.

Processing instructions / technical data sheets

See also data sheet: "BG-Chemie":

M050 Umgang mit gesundheitsgefährlichen Stoffen ²

Further information

Relevant changes

03. Hazardous components · 04. First-aid measures · 07. Handling and storage · 08. Exposure controls/personal protection · 09. Relevant safety data · 12. Ecological information · 14. Classification (ADR) · 15. Regulatory information

R-Phrases of components

The details refer to the separate ingredients, not to the product.

11 Highly flammable. 36 Irritating to eyes. 38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Page: 6 / 7

according to Regulation (EC) No. 1907/2006



Product name : SCHWEGO® CLEANER Z

Revision: 01.09.2009 **Version:** 1.0.0

Print date : 29.03.2010

67 Vapours may cause drowsiness and dizziness.

Contact

Dipl.-Chem. (FH) Gabriele Janssen · Tel. +49 (0) 22 25 / 92 26-12, Fax -48

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Page: 7 / 7