#### HYDROWASH

Page: 1

## 1. Наименование на веществото / препарата и на фирмата / предприятието

1. HummenoDanne	
Product name:	HYDROWASH
Product code:	C500
Use / description of product:	Flammable. Dangerous for the environment. Harmful. Liquid.
Company name:	E C S (Nottingham) Ltd Cross Road Annesley Cutting Annesley Nottinghamshire NG15 0AL Tel: 01623 720444 Fax: 01623 720445
2. Състав на препарата / информация за компонентите	
Hazardous ingredients:	LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY 50-70% EINECS: 265-185-4 CAS: 64742-82-1 [-] R10; [N] R51/53; [Xn] R65
•	LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. 30-50% EINECS: 265-199-0 CAS: 64742-95-6 [F+] R12; [Xi] R38; [N] R51/53; [Xn] R65
•	ISOPROPYLAMINE DODECYLBENZENE SULPHONATE 1-10% CAS: 26264-05-1 [Xi] R38; [Xi] R41
3. Описание на оп	асностите
Main hazards:	Flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed.
Other hazards:	In use, may form flammable / explosive vapour-air mixture.
4. Мерки за оказв	ане на първа помощ (Симптоми)
Skin contact:	There may be irritation and redness at the site of contact.
Eye contact:	There may be irritation and redness. The eyes may water profusely.
Ingestion:	There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest.

## 4. Мерки за оказване на първа помощ (Действия)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

#### HYDROWASH

Page: 2

Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion:	Wash out mouth with water. Do not induce vomiting. If conscious, give half a liter of water to drink immediately. Consult a doctor.
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

#### 5. Мерки при гасене на пожар

- **Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.
- **Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.
- **Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

#### 6. Мерки при аварийно изпускане

Personal precautions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorized personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.
Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labeled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

#### 7. Работа с веществото / препарата и съхранение

- Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.
- **Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment is not a source of ignition.

**Suitable packaging:** Must only be kept in original packaging.

#### 8. Контрол при експозиция и лични предпазни средства

Workplace exposure limits

WEL (8 hr exposure limit):	600mg/m3 (OES)
Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.
<b>Respiratory protection:</b>	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Impermeable gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Impermeable protective clothing.

#### HYDROWASH

Issued: Revision No:

Page: 3

#### 9. Физични и химични свойства

State:	Liquid
Colour:	Pale yellow
Odour:	Sweet-smelling
<b>Evaporation rate:</b>	Fast
Oxidising:	Non-oxidising (by EC criteria)
Solubility in water:	Miscible
Also soluble in:	Most organic solvents.
Viscosity:	Non-viscous
Boiling point/range°C:	180-217
Melting point/range°C:	<-50
Flammability limits %: lower:	0.6
upper:	7
Flash point <sup>o</sup> C:	38
Autoflammability°C:	>200
Vapour pressure:	0.04kPa
<b>Relative density:</b>	790kg/m
VOC g/l:	0.04kPa

#### 10. Стабилност и реактивоспособнос

11. Токсикологическа информация	
Haz. decomp. products:	In combustion emits toxic fumes.
Materials to avoid:	Strong oxidising agents. Strong acids.
Conditions to avoid:	Heat. Hot surfaces. Sources of ignition. Flames.
Stability:	Stable under normal conditions. Stable at room temperature.

 Hazardous ingredients:
 LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ORL RAT LD50 8400 mg/kg

 •
 ISOPROPYLAMINE DODECYLBENZENE SULPHONATE IVN RAT LD50 >2000 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

#### 12. Информация за околната среда

Persistence and degradability: Biodegradable.

- Bioaccumulative potential: No bioaccumulation potential.
- **Other adverse effects:** Negligible ecotoxicity.

### HYDROWASH

#### Issued: Revision No:

Page: 4

## 13. Третиране на отпадъците

<b>Disposal operations:</b>	Refer to local regulations referring disposal of waste substance.
NB:	The user's attention is drawn to the possible existence of regional or national regulationsregarding disposal.

## 14. Информация за транспортиране

ADR / RID

UN no:	1300	
Packing group:	II	
Shipping name:	TURPENTINE SUBSTITUTE	
Labelling:	3	
ADR Class:	3	
Classification code:	F1	
Hazard ID no:	33	
IMDG / IMO		
UN no	: 1300	Class: 3
Packing group	: II	EmS: F-E,S-E
Marine pollutant	: .	Labelling: 3
IATA / ICAO		
UN no	: 1300	Class: 3
Packing group	: П	<b>Packing instructions:</b> 305(P&CA); 307(CAO)
Labelling	: 3	

## 15. Информация, съгласно действащата нормативна уредба

	×
Hazard symbols:	Dangerous for the environment. Harmful.
Risk phrases:	R10: Flammable.
	R38: Irritating to skin.
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R65: Harmful: may cause lung damage if swallowed.
Safety phrases:	S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
Note:	The regulatory information given above only indicates the principal regulations specifically

#### HYDROWASH

Issued: Revision No:

Page: 5

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

#### 16. Друга информация

**Risk phrases used in s.2:** R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R12: Extremely flammable.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

## САМО ЗА ПРОМИШЛЕНА УПОТРЕБА