

SAFETY DATA SHEET

METER ROLL CLEANER

Issued: 01/09/00

Revision No: 1

Page: 1

E C S (Nottingham) Ltd

Cross Road

Annesley Cutting

Annesley

Nottinghamshire

NG15 0AL

Tel: 01623 720444

Fax: 01623 720445

1. Наименование на веществото / препаратата и на фирмата / предприятието

Product name: METER ROLL CLEANER

Product code: EC220

2. Състав на препаратата / информация за компонентите

Ingredient 1: XYLENE (MIXTURE OF ISOMERS) 30-60%

CAS: 1330-20-7

EINECS: 215-535-7

[-] R10; [Xn] R20/21; [Xi] R38;

Ingredient 2: LOW BOILING POINT MODIFIED NAPHTHA - NAPHTHA (PETROLEUM), SOLVENT-REFINED LIGHT 10-30%

CAS: 64741-84-0

EINECS: 265-086-6

[T] R45; [F+] R12; [Xi] R38; [N] R51/53; [Xn] R65;

Ingredient 3: LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. 10-30%

CAS: 64742-95-6

EINECS: 265-199-0

[T] R45; [F+] R12; [Xi] R38; [N] R51/53; [Xn] R65;

Ingredient 4: PROPAN-2-OL 10-30%

CAS: 67-63-0

EINECS: 200-661-7

[F] R11; [Xi] R36; [-] R67;

Contains: Xylene Mixture Of Isomers

Benzene cas no 71-43-2 will normally be present in trace amounts, but will always be

Less than the 0.1 w/w marker level in the 21st ATP to the dangerous substance directive.

SAFETY DATA SHEET

METER ROLL CLEANER

Issued: 01/09/00

Revision No: 1

Page: 2

Contains: aliphatic hydrocarbon classified R65

Contains: aromatic hydrocarbon classified R65

3. Описание на опасностите

Main hazards: Highly flammable. Irritating to eyes and skin. Harmful: may cause lung damage if swallowed.

4. Мерки за оказване на първа помощ (Симптоми)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. Мерки за оказване на първа помощ (Действия)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. See doctor if necessary.

Ingestion: Do not induce vomiting. Immediately rinse mouth and provide fresh air. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Seek medical attention.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Seek medical attention

5. Мерки при гасене на пожар

Extinguishing media: Water spray. Alcohol or polymer foam. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus.

6. Мерки при аварийно изпускане

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand.

7. Работа с веществото / препарата и съхранение

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

8. Контрол при експозиция и лични предпазни средства

SAFETY DATA SHEET

METER ROLL CLEANER

Issued: 01/09/00

Revision No: 1

Page: 3

Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Adequate ventilation
Hand protection:	Protective gloves.
Eye protection:	Safety goggles. Ensure eye bath is to hand.
Skin protection:	Chemical resistant standard issue work clothes.

9. Физични и химични свойства

State:	Liquid
Colour:	Colourless
Odour:	Perceptible odour
Solubility in water:	Insoluble
Boiling point/range°C:	90-120
Flammability limits %: lower:	1
upper:	8
Flash point°C:	11
Autoflammability°C:	400
Relative density:	82

10. Стабилност и реактивоспособност

Stability:	Stable under normal conditions.
Conditions to avoid:	Sources of ignition.
Materials to avoid:	Oxidising agents.
Haz. decomp. products:	In combustion emits toxic fumes.

11. Токсикологическа информация

Ingredient 2:	LOW BOILING POINT MODIFIED NAPHTHA - NAPHTHA (PETROLEUM), SOLVENT-REFINED LIGHT
Ingredient 3:	LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.
Ingredient 4:	PROPAN-2-OL
	IVN RAT LD50 1088mg/kg
	ORL MUS LD50 3600mg/kg
	ORL RAT LD50 5045mg/kg
	SCU MUS LDLO 6gm/kg

12. Информация за околната среда

13. Третиране на отпадъците

SAFETY DATA SHEET

METER ROLL CLEANER

Issued: 01/09/00

Revision No: 1

Page: 4

Waste disposal: Disposal should be dealt with only by qualified personnel familiar with the specific substance.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. Информация за транспортиране

ADR / RID

UN no: 1993

ADR Class: 3

Hazard ID no: 33

Labelling: 3

IMDG / IMO

UN no: 1993

Class: 3.2

Packing group: II

EmS: 3-07

Marine pollutant: YES

Labelling: 3 FLAMMABLE LIQUID

IATA / ICAO

UN no: 1993

Class: 3

Packing group: II

Packing instructions: 307

Quantity 60 L

Labeling: 3 FLAMMABLE LIQUID

15. Информация, съгласно действащата нормативна уредба

Hazard symbols: Harmful.

Highly flammable.

Risk phrases: R11: Highly flammable.

R36/38: Irritating to eyes and skin.

R65: Harmful: may cause lung damage if swallowed.

Safety phrases: S2: Keep out of the reach of children.

S23: Do not breathe...

S16: Keep away from sources of ignition - No smoking.

SAFETY DATA SHEET

METER ROLL CLEANER

Issued: 01/09/00

Revision No: 1

Page: 5

S33: Take precautionary measures against static discharges.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Note:

The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. Друга информация

Risk phrases used in s.2:

R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R45: May cause cancer.

R12: Extremely flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R11: Highly flammable.

R36: Irritating to eyes.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

САМО ЗА ПРОМИШЛЕНА УПОТРЕБА