



Printing date 07.09.2010 Revision: 03.09.2010

1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: HYDROWASH 12X1L

· Article number: 141042

· Application of the substance / the preparation: Washing fluid for offset printing machines

· Manufacturer/Supplier:

FUJIFILM Europe NV

EUROPARK-NOORD 21-22

9100 SINT-NIKLAAS

BELGIUM

TEL: +32 3 760 02 00 FAX: +32 3 776 91 22

- · Further information obtainable from: productsafety@fujifilm.eu
- · Information in case of emergency: +32 3 760 02 00

2 Hazards identification

· Hazard description:





Xn Harmful

N Dangerous for the environment

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

R 10 Flammable.

R 37 Irritating to respiratory system.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed. R 65

R 66 Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- · Chemical characterization
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compo	nents:	
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	50-70%
EINECS: 265-185-4	Xn, X N; R 10-51/53-65-66-67	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	15-30%
EINECS: 265-199-0	Xn, Xi, Xi, N; R 10-37-51/53-65-66-67	
	(Con	t. on page 2)





Printing date 07.09.2010 Revision: 03.09.2010

Trade name: HYDROWASH 12X1L

		Cont. from page 1)
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene Xn, Xi, № N; R 10-20-36/37/38-51/53	7-15%
CAS: 108-67-8 EINECS: 203-604-4	mesitylene	1-5%
CAS: 1330-20-7 EINECS: 215-535-7	xylene Xn, Xi; R 10-20/21-38	1-5%
CAS: 98-82-8 EINECS: 202-704-5	cumene X Xn, X Xi, B N; R 10-37-51/53-65	0.1-1%

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.

5 Fire-fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

- · Handling:
- · Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

(Cont. on page 3)





Printing date 07.09.2010 Revision: 03.09.2010

Trade name: HYDROWASH 12X1L

(Cont. from page 2)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data: see item 7.

· Addii	tional information about design of technical facilities: No further data, see item 7.		
· Ingre	dients with limit values that require monitoring at the workplace:		
95-63	95-63-6 1,2,4-trimethylbenzene		
WEL	Long-term value: 125 mg/m³, 25 ppm ILV		
108-6	7-8 mesitylene		
WEL	Long-term value: 125 mg/m³, 25 ppm ILV		
1330-	1330-20-7 xylene		
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV		
98-82-8 cumene			
WEL	Short-term value: 250 mg/m³, 50 ppm Long-term value: 125 mg/m³, 25 ppm Sk		

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

(Cont. on page 4)





Printing date 07.09.2010 Revision: 03.09.2010

Trade name: HYDROWASH 12X1L

(Cont. from page 3)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information	
· General information	
Form:	Liquid
Colour:	Yellow
Odour:	Characteristic
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	
· Flash point:	42℃
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Density at 20℃:	0.811 g/cm³
· Solubility in / Miscibility with water:	Emulsifiable.
· Solvent content: VOC (EC)	96.81 %

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided:
 - No decomposition if used according to specifications.
- · Materials to be avoided:
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: Carbon monoxide and carbon dioxide





Printing date 07.09.2010 Revision: 03.09.2010

Trade name: HYDROWASH 12X1L

(Cont. from page 4)

11 Toxicological information

· Acute toxicity:

· LD/LC50	· LD/LC50 values relevant for classification:		
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6800 mg/kg (rat)	
Dermal	LD50	>3400 mg/kg (rab)	
Inhalative	LC50/4 h	>10.2 mg/l (rat)	
95-63-6 1,	95-63-6 1,2,4-trimethylbenzene		
Oral	LD50	5000 mg/kg (rat)	
98-82-8 cı	98-82-8 cumene		
Oral	LD50	1400 mg/kg (rat)	
Dermal	LD50	12300 mg/kg (rabbit)	
Inhalative	LC50/4 h	24.7 mg/l (mouse)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

	· European waste catalogue	
	07 00 00	WASTES FROM ORGANIC CHEMICAL PROCESSES
	07 06 00	wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics
•		(Cont. on page 6)

— GB





Printing date 07.09.2010 Revision: 03.09.2010

Trade name: HYDROWASH 12X1L

(Cont. from page 5)

07 06 04* other organic solvents, washing liquids and mother liquors

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 Flammable liquids.

Danger code (Kemler): 30
UN-Number: 1993
Packaging group: III
Hazard label: 3

· Description of goods: 1993 FLAMMABLE LIQUID, N.O.S. (ALKYL C3 BENZENES, CYMENES,

TURPENTINE SUBSTITUTE)

· Tunnel restriction code D/E

· Maritime transport IMDG:





IMDG Class: 3
UN Number: 1993
Label 3
Packaging group: III
EMS Number: F-E,S-E
Marine pollutant: Yes

Symbol (fish and tree)

· Proper shipping name: FLAMMABLE LIQUID, N.O.S. (ALKYL C3 BENZENES, CYMENES,

TURPENTINE SUBSTITUTE)

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3 · UN/ID Number: 1993 · Label 3 · Packaging group: III

(Cont. on page 7)



Page 7/8

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 03.09.2010

Trade name: HYDROWASH 12X1L

(Cont. from page 6)

• Proper shipping name: FLAMMABLE LIQUID, N.O.S. (ALKYL C3 BENZENES, CYMENES, TURPENTINE SUBSTITUTE)

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





Xn Harmful

N Dangerous for the environment

· Hazard-determining components of labelling:

mixture of hydrocarbons

· Risk phrases:

- 10 Flammable.
- 37 Irritating to respiratory system.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 23 Do not breathe vapour
- 24 Avoid contact with skin.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 57 Use appropriate container to avoid environmental contamination.
- 60 This material and its container must be disposed of as hazardous waste.
- 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

10 Flammable.

20 Harmful by inhalation.

20/21 Harmful by inhalation and in contact with skin. 36/37/38 Irritating to eyes, respiratory system and skin.

37 Irritating to respiratory system.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

65 Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

(Cont. on page 8)



Page 8/8

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010 Revision: 03.09.2010

Trade name: HYDROWASH 12X1L

(Cont. from page 7)

Vapours may cause drowsiness and dizziness.

- Creation Date 15.06.2009

·* Data modified compared to previous version.

GR -