

Page 1/7

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 03.09.2010

1 Identification of the substance/preparation and of the company/undertaking

· Product details

Trade name: HYDROWASH 60 200L

• Article number: 141222

· Application of the substance / the preparation: Washing fluid for offset printing machines

 Manufacturer/Supplier: FUJIFILM Europe NV EUROPARK-NOORD 21-22 9100 SINT-NIKLAAS BELGIUM TEL: +32 3 760 02 00 FAX: +32 3 776 91 22

• Further information obtainable from: productsafety@fujifilm.eu • Information in case of emergency: +32 3 760 02 00

2 Hazards identification

· Hazard description:



Xn Harmful

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- R 65 Harmful: may cause lung damage if swallowed.
- R 66 Repeated exposure may cause skin dryness or cracking.
- Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

· Chemical characterization

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy Xn; R 65-66	70-90)%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. 🕱 Xn, 🔀 Xi, 🌄 N; R 10-37-51/53-65-66-67	7-15	%
	1,2,4-trimethylbenzene 🗙 Xn, 🗙 Xi, 🏪 N; R 10-20-36/37/38-51/53	3-7%	6
		(Cont. on pag	je 2) — G



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 03.09.2010

Page 2/7

Trade name: HYDROWASH 60 200L

	(C	ont. from page 1)
CAS: 108-67-8	mesitylene	1-5%
EINECS: 203-604-4	🗙 Xi, 🧏 N; R 10-37-51/53	
CAS: 91-20-3	naphthalene	0.1-1%
	Carc. Cat. 3; 🗙 Xn, 🏪 N; R 22-40-50/53	
CAS: 103819-01-8	Fat alchol alcoxylate polymer	0.1-1%
	🗙 Xi, 🏪 N; R 38-50	
CAS: 98-82-8	cumene	0.1-1%
EINECS: 202-704-5	🗙 Xn, 🗙 Xi, 🟪 N; R 10-37-51/53-65	
• Additional information: For the wording of the listed risk phrases refer to section 16.		

4 First aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; call for medical help immediately.

5 Fire-fighting measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Person-related safety precautions: Not required.
- Measures for environmental protection: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.

Store only in the original receptacle.

· Information about storage in one common storage facility: Not required.

GB



Page 3/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Revision: 03.09.2010

(Cont. from page 2)

Trade name: HYDROWASH 60 200L

• Further information about storage conditions: Keep container tightly sealed.

· Storage class: 10

Printing date 07.09.2010

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

95-63-6 1,2,4-trimethylbenzene

WEL Long-term value: 125 mg/m³, 25 ppm

108-67-8 mesitylene

ILV

WEL Long-term value: 125 mg/m³, 25 ppm

· Additional information: The lists valid during the making were used as basis.

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.

Do not innaic gases / fames / acro

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

(Cont. on page 4)

GB



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 03.09.2010

Trade name: HYDROWASH 60 200L

(Cont. from page 3)

General Information	
Form:	Liquid
Colour:	Yellow
Odour:	Characteristic
Change in condition	
Melting point/Melting range:	
Boiling point/Boiling range:	Undetermined.
· Flash point:	58°C
 Danger of explosion: 	Product does not present an explosion hazard.
· Density at 20℃:	0.82 g/cm ³
· Solubility in / Miscibility with	
water:	Emulsifiable.
· Solvent content:	
VOC (EC)	96.85 %

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided:

- No decomposition if used according to specifications.
- · Materials to be avoided:
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

· Acute toxicity:

· LD/LC50	· LD/LC50 values relevant for classification:			
64742-95-6 Solvent naphtha (petroleum), light arom.				
Oral	LD50	>6800 mg/kg (rat)		
Dermal	LD50	>3400 mg/kg (rab)		
Inhalative	LC50/4 h	>10.2 mg/l (rat)		
95-63-6 1,	95-63-6 1,2,4-trimethylbenzene			
Oral	LD50	5000 mg/kg (rat)		
91-20-3 na	91-20-3 naphthalene			
Oral	LD50	490 mg/kg (rat)		
Dermal	LD50	5000 mg/kg (rat)		
 Primary in on the sk on the eye Sensitization 	in: No irrita e: No irrita	ant effect.	(Cont. on page 5)	

Page 4/7



Page 5/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Revision: 03.09.2010

(Cont. from page 4)

Trade name: HYDROWASH 60 200L

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

12 Ecological information

- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

07 00 00 WASTES FROM ORGANIC CHEMICAL PROCESSES

07 06 00 wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics 07 06 04^{*} other organic solvents, washing liquids and mother liquors

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



• ADR/RID class: 3 Flammable liquids.

- Danger code (Kemler): 30
- · **UN-Number:** 1268
- · Packaging group: III
- Hazard label: 3
- Description of goods: 1268 PETROLEUM DISTILLATES, N.O.S.

(Cont. on page 6)



Page 6/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2010

Trade name: HYDROWASH 60 200L

Revision: 03.09.2010

	(0	Cont. from page 5)
· Tunnel restriction co	de D/E	
· Maritime transport IN	IDG:	
· IMDG Class:	3	
· UN Number:	1268	
· Label	3	
 Packaging group: 	III	
· EMS Number:	F-E,S-E	
 Marine pollutant: 	No	
 Proper shipping nam 	e: PETROLEUM DISTILLATES, N.O.S.	
· Air transport ICAO-T	and IATA-DGR:	
· ICAO/IATA Class:	3	
· UN/ID Number:	1268	
· Label	3	
 Packaging group: 	III	
 Proper shipping nam 	e: PETROLEUM DISTILLATES, N.O.S.	

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xn Harmful

- Hazard-determining components of labelling: mixture of hydrocarbons
- · Risk phrases:
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.

Safety phrases:

- 23 Do not breathe vapour
- 24 Avoid contact with skin.

(Cont. on page 7)

⁻ GB



Page 7/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Revision: 03.09.2010

(Cont. from page 6)

Trade name: HYDROWASH 60 200L

57 Use appropriate container to avoid environmental contamination.

62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

16 Other information

Printing date 07.09.2010

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

- 10 Flammable.
- 20 Harmful by inhalation.
- 22 Harmful if swallowed.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 37 Irritating to respiratory system.
- 38 Irritating to skin.
- 40 Limited evidence of a carcinogenic effect.
- 50 Very toxic to aquatic organisms.
- 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- · Creation Date 13.07.2009
- \cdot * Data modified compared to previous version.

GB -