



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2010 Revision: 21.09.2010

1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: W 1930 SPEZIAL/45 25KG

· Article number: 12290D21

· Application of the substance / the preparation: Dispersion varnish for offset printing

Manufacturer/Supplier:
 FUJIFILM Europe NV
 EUROPARK-NOORD 21-22

9100 SINT-NIKLAAS

BELGIUM

TEL: +32 3 760 02 00 FAX: +32 3 776 91 22

· Further information obtainable from: productsafety@fujifilm.eu

· Information in case of emergency: +32 3 760 02 00

2 Hazards identification

- · Hazard description: Not applicable.
- · Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- · Chemical characterization
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
	sodiumdioctylsulfosuccinate	1-5%		
EINECS: 209-406-4	Xi; R 38-41			
CAS: 85711-69-9	sulfonic acids, C13-17-sec alkane, sodium salts	1-5%		
	Xi; R 38-41			
CAS: 1336-21-6		0.1-1%		
EINECS: 215-647-6	C, N N; R 34-50	ļ		

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

GB



Page 2/5

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2010 Revision: 21.09.2010

Trade name: W 1930 SPEZIAL/45 25KG

(Cont. from page 1)

5 Fire-fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Protective equipment: No special measures required.

6 Accidental release measures

- · Person-related safety precautions: Not required.
- Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Additional information: No dangerous substances are released.

7 Handling and storage

- · Handling:
- · Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from frost.
- · Storage class: 12

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Cont. on page 3)





Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2010 Revision: 21.09.2010

Trade name: W 1930 SPEZIAL/45 25KG

(Cont. from page 2)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

9 Physical	and	chemical	properties
------------	-----	----------	------------

General Information Form: Colour: Light beige Odour: Mild Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 100℃ Flash point: Not applicable. Danger of explosion: Product does not present an explosion hazard. Density at 20℃: 1.03 g/cm³ Solubility in / Miscibility with water: Dispersible. pH-value at 20℃: 7.9 Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) Solvent content: VOC (EC) 0.78 %	or nyordar arra orioniroa. proportioo				
Colour: Light beige Mild Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 100℃ Flash point: Not applicable. Danger of explosion: Product does not present an explosion hazard. Density at 20℃: 1.03 g/cm³ Solubility in / Miscibility with water: Dispersible. pH-value at 20℃: 7.9 Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) Solvent content:	· General Information				
Odour: Mild Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 100℃ Flash point: Not applicable. Danger of explosion: Product does not present an explosion hazard. Density at 20℃: 1.03 g/cm³ Solubility in / Miscibility with water: Dispersible. pH-value at 20℃: 7.9 Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) Solvent content:					
Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 100℃ Flash point: Not applicable. Danger of explosion: Product does not present an explosion hazard. Density at 20℃: 1.03 g/cm³ Solubility in / Miscibility with water: Dispersible. pH-value at 20℃: 7.9 Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) Solvent content:	Colour:	Light beige			
Melting point/Melting range: Undetermined. Boiling point/Boiling range: 100℃ Flash point: Not applicable. Danger of explosion: Product does not present an explosion hazard. Density at 20℃: 1.03 g/cm³ Solubility in / Miscibility with water: Dispersible. pH-value at 20℃: 7.9 Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) Solvent content:	Odour:	Mild			
Boiling point/Boiling range: 100℃ · Flash point: Not applicable. · Danger of explosion: Product does not present an explosion hazard. · Density at 20℃: 1.03 g/cm³ · Solubility in / Miscibility with water: Dispersible. · pH-value at 20℃: 7.9 · Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) · Solvent content:	· Change in condition				
 Flash point: Not applicable. Danger of explosion: Product does not present an explosion hazard. Density at 20℃: 1.03 g/cm³ Solubility in / Miscibility with water: Dispersible. pH-value at 20℃: 7.9 Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) Solvent content: 	Melting point/Melting range	: Undetermined.			
Danger of explosion: Density at 20℃: Solubility in / Miscibility with water: Dispersible. Product does not present an explosion hazard. 1.03 g/cm³ Dispersible. Ph-value at 20℃: 7.9 Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4)	Boiling point/Boiling range:	100℃			
Density at 20℃: Solubility in / Miscibility with water: Dispersible. PH-value at 20℃: Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) Solvent content:	· Flash point:	Not applicable.			
· Solubility in / Miscibility with water: · pH-value at 20℃: · Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) · Solvent content:	· Danger of explosion:	Product does not present an explosion hazard.			
water: Dispersible. · pH-value at 20℃: 7.9 · Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) · Solvent content:	· Density at 20℃:	1.03 g/cm ³			
· pH-value at 20℃: 7.9 · Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) · Solvent content:	· Solubility in / Miscibility with				
· Viscosity: Kinematic at 20℃: 20-100 s (DIN 53211/4) · Solvent content:	water:	Dispersible.			
Kinematic at 20℃: 20-100 s (DIN 53211/4) Solvent content:	· pH-value at 20℃:	7.9			
- Solvent content:	· Viscosity:				
	Kinematic at 20℃:	20-100 s (DIN 53211/4)			
VOC (EC) 0.78 %	· Solvent content:				
•	VOC (EC)	0.78 %			

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Materials to be avoided:
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

зв.



Page 4/5

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2010 Revision: 21.09.2010

Trade name: W 1930 SPEZIAL/45 25KG

(Cont. from page 3)

11 Toxicological information

· Acute toxicity:

Primary irritant effect:

on the skin: No irritant effect.on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

12 Ecological information

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation Smaller quantities can be disposed of with household waste.

· European waste catalogue		
	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS	
08 01 00	wastes from MFSU and removal of paint and varnish	
08 01 12	waste paint and varnish other than those mentioned in 08 01 11	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · Land transport ADR/RID (cross-border)
- ADR/RID class:
- · Maritime transport IMDG:
- · IMDG Class:
- · Marine pollutant: No

(Cont. on page 5)



Page 5/5

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2010 Revision: 21.09.2010

Trade name: W 1930 SPEZIAL/45 25KG

(Cont. from page 4)

- · Air transport ICAO-TI and IATA-DGR:
- · ICAO/IATA Class: -

15 Regulatory information

· Labelling according to EU guidelines:

Observe the general safety regulations when handling chemicals.

The product is not subject to identification regulations under EU Directives and the Ordinance on Hazardous Materials (German GefStoffV).

· Special labelling of certain preparations:

Safety data sheet available for professional user on request.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant R-phrases
- 34 Causes burns.
- 38 Irritating to skin.
- 41 Risk of serious damage to eyes.
- 50 Very toxic to aquatic organisms.
- · Creation Date 04.09.2009
- · * Data modified compared to previous version.

GB